










## Pattern No.: 1810061 - Yarn Quality (Schuh) Oberteil(e)

A	B	C	D	E	D	C	B	A
				8		8A  1x Nm 30/2   Protection thread   -	<	
				7				
				6		6A  1x 167 dtex+2x dtex167 f32 x2   KE-60+W8983   PES+100% PES   EMS-Griltech+Zimmermann	<+<<	
	>+>>	5A  1x 167 dtex+2x dtex167 f32 x2   KE-60+W8983   PES+100% PES   EMS-Griltech+Zimmermann		5		5B  1x dtex 334 f72 x4   PES HE VW   100% PES   TWD Fibres	<	
	>	4A  1x dtex 334 f72 x4   PES HE VW   100% PES   TWD Fibres		4		4B  1x 167 dtex+2x dtex167 f32 x2   KE-60+W8983   PES+100% PES   EMS-Griltech+Zimmermann	<+<<	
	>+>>	3A  1x 167 dtex+2x dtex167 f32 x2   KE-60+W8983   PES+100% PES   EMS-Griltech+Zimmermann		3				
	>	2A  -   -   Comb thread   -		2				
	>	1A  -   -   Draw separation thread   -		1				

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track



Normal



Normal-ADF



Intarsia type 1



Intarsia type 2



Plating Yf. N



Double-Arm Plating Yf.



Plating\_w\_2->1



Plating\_w\_2->2

**Pattern No.: 1810061**

**Other Requirements:**

Die Fadenführer mit dem Schußgarn (4A u. 5B) benötigen gröbere Fadenführernüßchen der Feinheit E7-8

---