

## Pattern No.: 1210212 - Yarn Quality V-Teil(e)

A	B	C	D	E	D	C	B	A
						8B  1x Nm 30/2   Protection thread   -	<	
	>	7A  1x Nm 30/2   Protection thread   -						
Storage >	>	6A  1x Nm 6,2   Airsilver   67% VI, 33% WV   IGEA						
Friction >	>	5A  1x 80 den   Monofil T   100% PA   Colorific						
						4B  1x 80 den   Monofil T   100% PA   Colorific	<	Friction <
						3A  1x Nm 6,2   Airsilver   67% VI, 33% WV   IGEA	<	Storage <
	>	2A  1x   Comb thread   Zimmermann				2B  1x Nm 6,2   Airsilver   67% VI, 33% WV   IGEA	<	Storage <
	>	1A  1x   Draw separation thread   -						

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track



Normal



Normal-ADF



Intarsia type 1



Intarsia type 2



Plating Yf. N



Double-Arm Plating Yf.



Plating\_w\_2->1



Plating\_w\_2->2

**Pattern No.: 1210212**

**Other Requirements:**

Devoreumbausatz muss hinten eingebaut sein. Siehe Systembelegung.

Devoré Mustertechnologie.

Maschine muss vor der Produktion mit den entsprechenden Schlossteilen ausgestattet sein. Hintere beiden Schlösser S2(Mitte)/S3(Rechts).

---

**Plush / devoré knit , new**

