

Pattern No.: 1210120 - Yarn Quality V-Teil(e)

A	B	C	D	E	D	C	B	A
						8A 1x Nm 34/2 Protection thread -	<	Friction <
Friction >	>	7A 1x Nm 34/2 Protection thread -						
Friction >	>	6A 1x Nm 46 Image 80% VI, 20% PES Lineapiù						
Friction >	>>	4A 2x Nm 22 Camelot 44% WM, 37% PA, 19% WV Lineapiù				4B 2x Nm 46 Image 80% VI, 20% PES Lineapiù	<<	Friction <
						3A 1x Nm 46 Image 80% VI, 20% PES Lineapiù	<	Friction <
	>	2A - Comb thread -				2B 2x Nm 22 Camelot 44% WM, 37% PA, 19% WV Lineapiù	<<	Friction <
	>	1A - Draw separation thread -						

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track



Normal



Normal-ADF



Intarsia type 1



Intarsia type 2



Plating Yf. N



Double-Arm Plating Yf.








Plating_w_2->1



Plating_w_2->2






Pattern No.: 1210120 - Yarn Quality V-Teil(e) links

A	B	C	D	E	D	C	B	A
				8		8A 1x Nm 34/2 Protection thread -	<	Friction <
				7				
				6				
Friction >	>>	5A 2x Nm 46 Image 80% VI, 20% PES Lineapiù		5				
Friction >	>>	4A 2x Nm 22 Camelot 44% WM, 37% PA, 19% WV Lineapiù		4				
				3				
	>	2A - Comb thread -		2				
	>	1A - Draw separation thread -		1				

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track



Pattern No.: 1210120 - Yarn Quality V-Teil(e) rechts

A	B	C	D	E	D	C	B	A		
				8				8A 1x Nm 34/2 Protection thread -	<	Friction <
				7						
				6						
				5						
				4				4A 2x Nm 46 Image 80% VI, 20% PES Lineapiù	<<	Friction <
				3						
	>	2A - Comb thread -		2				2B 2x Nm 22 Camelot 44% WM, 37% PA, 19% WV Lineapiù	<<	Friction <
	>	1A - Draw separation thread -		1						

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track



Pattern No.: 1210120 - Yarn Quality R-Teil(e)

A	B	C	D	E	D	C	B	A
						8A 1x Nm 34/2 Protection thread -	<	Friction <
Friction >	>	7A 1x Nm 34/2 Protection thread -						
Friction >	>	6A 1x Nm 46 Image 80% VI, 20% PES Lineapiù						
Friction >	>>	5A 2x Nm 46 Image 80% VI, 20% PES Lineapiù						
Friction <	>>	4A 2x Nm 22 Camelot 44% WM, 37% PA, 19% WV Lineapiù						
						3A 1x Nm 46 Image 80% VI, 20% PES Lineapiù	<	Friction <
	>	2A - Comb thread -				2B 2x Nm 22 Camelot 44% WM, 37% PA, 19% WV Lineapiù	<<	Friction <
	>	1A - Draw separation thread -						

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track

