Pattern No.: 2110030 - Yarn Quality V-Teil(e) SEN_1

A	B	C	D	E	D	C	B	A
				8		8A| 1x | Protection thread | - |	<	
				7				
				6		6A, NAVY| 2x Nm 50/2 | Jump | 68% VI, 32% PBT | Sesia |	<<	Friction <
				5				
				4		4A, LIGHT GREEN| 1x Nm 50/3 | KbA BW | 100% CO | Gebr. Otto |	<	Friction <
				3		3A, NAVY| 2x Nm 50/2 | Jump | 68% VI, 32% PBT | Sesia |	<<	Friction <
	>	2A| 1x | Comb thread | - |		2				
	>	1A| 1x | Draw separation thread | - |		1				

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track

Normal Normal-ADF Intarsia type 1 Intarsia type 2 Plating Yf. N Double-Arm Plating Yf. Plating_w_2->1 Plating_w_2->2

Pattern No.: 2110030 - Yarn Quality R-Teil(e) SEN_1

A	B	C	D	E	D	C	B	A
				8		8A| 1x | Protection thread | - |	<	
				7				
				6				
				5				
				4		4A, LIGHT GREEN| 1x Nm 50/3 | KbA BW | 100% CO | Gebr. Otto |	<	Friction <
				3		3A, NAVY| 2x Nm 50/2 | Jump | 68% VI, 32% PBT | Sesia |	<<	Friction <
	>	2A| 1x | Comb thread | - |		2				
	>	1A| 1x | Draw separation thread | - |		1				

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track

Normal | Normal-ADF | Intarsia type 1 | Intarsia type 2 | Plating Yf. N | Double-Arm Plating Yf. | Plating_w_2->1 | Plating_w_2->2

Pattern No.: 2110030 - Yarn Quality Ärmel links 1 SEN_1

A	B	C	D	E	D	C	B	A
				8		8A| 1x | Protection thread | - |	<	
				7				
Friction >	>>	6A, NAVY| 2x Nm 50/2 | Jump | 68% VI, 32% PBT | Sesia |		6				
				5				
				4		4A, LIGHT GREEN| 1x Nm 50/3 | KbA BW | 100% CO | Gebr. Otto |	<	Friction <
				3		3A, NAVY| 2x Nm 50/2 | Jump | 68% VI, 32% PBT | Sesia |	<<	Friction <
	>	2A| 1x | Comb thread | - |		2				
	>	1A| 1x | Draw separation thread | - |		1				

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track

Normal Normal-ADF Intarsia type 1 Intarsia type 2 Plating Yf. N Double-Arm Plating Yf. Plating_w_2->1 Plating_w_2->2

Pattern No.: 2110030 - Yarn Quality Ärmel rechts 1 SEN_1

A	B	C	D	E	D	C	B	A
			8			8A| 1x | Protection thread | - |	<	
			7					
			6					
			5					
			4			4A, LIGHT GREEN| 1x Nm 50/3 | KbA BW | 100% CO | Gebr. Otto |	<	Friction <
			3			3A, NAVY| 2x Nm 50/2 | Jump | 68% VI, 32% PBT | Sesia |	<<	Friction <
	>	2A| 1x | Comb thread | - |	2					
	>	1A| 1x | Draw separation thread | - |	1					

A: Feed Wheel B: Feed C: Yarn count D: Feeder E: Track

Normal Normal-ADF Intarsia type 1 Intarsia type 2 Plating Yf. N Double-Arm Plating Yf. Plating_w_2->1 Plating_w_2->2